



Effective: 04/05/2017

Technical Data Sheet

Supersedes: 07/08/2007

Automotive Aftermarket Division

3M 55535 Finish Control Spray

1) Part Numbers

55535

2) Description and end uses

3M Finish Control Spray is the ideal product to check the progress in any finishing operation, particularly to see if micro scratches from previous sanding steps are as polished out as they should be.

It is specially designed and tested to be compatible with all cured refinish paint systems, leaving any surface clean and ready for inspection.

Particularly recommended to always use after the first compounding step.

Product highlights:

- Reliably removes any compound residue
- Reduces the risk of undetected micro scratches coming back
- Helps to achieve the perfect finish result
- Also suitable for a quick surface clean, leaving no streaks

3) Physical Properties

Base	:	Water-based
Colour	:	White
Consistency	:	Foam
Solvent	:	Water
Propellant	:	Hydrocarbon
VOC	:	50g
Application temperature	:	+15°C to +30°C



4) Directions for Use

- Wait until compounded/polished area has cooled off
- Shake can before use
- Apply a liberal amount of Control Spray from a distance of 20-30 cm to surface
- Wipe off with a high performance wipe (ie. 34568 3M Disposable Polishing Wipe or 50400 Polishing Wipe)
- Control for residual sanding scratches. If these scratches are still visible, repeat previous compound step

CAUTION: Do not apply to hot surfaces (>30°C)

5) Storage

Store in a cool dry place. Storage temperature must not exceed 50°C.

Shelf life is 24 months from date of manufacture under normal storage conditions. Refer to "Lot Number" and "Best Before Date" on can.

6) Safety

Please refer to the Material Safety Data Sheet or contact your local 3M Toxicology Department.

3M 55535 Finish Control Spray is designed FOR PROFESSIONAL INDUSTRIAL USE ONLY.

7) Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of reliability relating to this product are governed by the Terms of Sale subject, where applicable, to the prevailing law.



Technical Data Sheet

Effective: 04/05/2017

Supersedes: 07/08/2007

For Additional Health and Safety Information

Denmark

3M a/s
Automotive Aftermarket
Hannemanns Allé 53
2300 København S
Tel: 43 48 01 00
3mkundeservicedk@mmm.com
www.3MAuto.dk

Finland

Suomen 3M Oy
Automotive Aftermarket
Keilaranta 6
02150 Espoo
Tel: 09 5252 1
tilaukset@mmm.com
www.3M.fi/autotuotteet

Norway

3M Norge AS
Automotive Aftermarket
Kanalveien 2
2004 Lillestrøm
Telefon: 06384
www.3m.no/auto
kundeservice@mmm.com

Sweden

3M Svenska AB
Automotive Aftermarket
Bileftermarknad
19189 Sollentuna
Tel. 08-922100
kundservice@mmm.com
3M.se/bileftermarknad