

Technical Data Sheet

XT4039/00

MATTING PASTE FOR POLYURETHANES

Supersedes previous issue dated 05/07/96

DATE 09/09/97

Use:	As additive for clear and pigmented polyurethane topcoats to increase matt.
------	---

Technical characteristics:

Solids content (%):	25 ± 1
Specific gravity (kg/l):	0.947 ± 0.030
Viscosity (DIN 4 at 20°C):	22" ± 5"
Shelf-life:	If the product is properly stored, shelf-life is unlimited. After long periods of storage, always check homogeneity and stir well before use to eliminate any possible sediment.

General characteristics

XT4039/00 is a matting paste to be added to polyurethane topcoats to correct gloss level.

To avoid problems of uniformity, add XT4039/00 paste using a mechanical stirrer. If necessary, filter the mixed product using a nylon screen with 30-50 micron mesh.

Dosages

XT4039/00 can be added to the coating at 1-10%.

As a guideline, the following quantities should be used (expressed with respect to part A):

- from 50 gloss to 40 gloss about 1% of XT4039/00
- from 40 gloss to 30 gloss about 3% of XT4039/00
- from 30 gloss to 20 gloss about 5% of XT4039/00
- from 20 gloss to 10 gloss about 10% of XT4039/00

N.B.: The product is not compatible with acrylic-polyurethane coatings.