

COMPANY WITH MANAGEMENT SYSTEM - UNI EN ISO 9001 -- UNI EN ISO 14001 - Sherwin-Williams Italy S.r.I. – con unico socio Via del Fiffo, 12 - 40065 Pianoro (BO) - Italia - C.P. 18 tel. +39 051 770 511 - fax +39 051 777 437 www.sayerlack.com Cod. Fisc. e Reg. Impr. Bo 08866930152 P. IVA: IT 00494251200 - R.E.A. n. 313180 Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Company under the direction and coordination of The Sherwin-Williams Company, USA

# Technical Data Sheet

QHL6284/00 CATALIZZATORE PER LIQUID LENS

DATE 11/18/2016

#### Area of use

Casting resins

# **Technical characteristics**

| Binders           | Amino resins |                    |
|-------------------|--------------|--------------------|
| Density           | 0,95 (±0,03) | kg/l               |
| Flashpoint        | 128°C        | Method: Closed cup |
| Solid content     | 100          | % by weight        |
| Storage stability | 12 months    | at 30°C max        |

### **General Characteristics**

| Transparency: | very good |
|---------------|-----------|
| Yellowing:    | low       |

## **Special instructions**

The product is sensitive to humidity: Keep in closed containers.

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION. IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.