

Technical Data Sheet

OLV2322/00 NATURAL OIL

Supersedes previous issue dated 03.14.19

DATE 15 April 2019

Area of use:	Various supports. Approved for Ikea IOS-MAT-0128 (Food contact)
Method of use:	Spray, brush, wiping, dipping.
Thinning:	ready to use

Technical characteristics

Solids content (%):	100
Specific gravity (kg/l):	0.93 ± 0.030
Viscosity (DIN 4 at 20°C):	19" ± 1"

General characteristics

Recommended application weight (gr/m ²):	from 30 to 70
Drying time (50 g/m ² at 20°C):	stackable 48 - 72h
Number of coats:	2-more
Shelf-life (months):	12

We recommend to stir the product before application.

It is a natural oil, penetrates into the wood fiber and pores giving brilliance, keeping a natural effect. Oil composition allows wood transpiration.

OLV2322/00 meets the requirements laid down in the Ikea IOS-MAT-0128 (food contact).

Wood finished with OLV2322/00 needs a periodic maintenance.

Soaked cloth could give auto-ignition! Wet them with water before trashing.

Application:

OLV2322/00 can be applied by manual spray, brush, cloth or dipping. We suggest to apply 30 - 70 gr/sqm. Once applied we suggest to remove the excess of product with a clean cloth. Between layers wait at least 24 hours, then kindly sand with ultrafine sandpaper or steel-wool (0000). Last layer needs more drying time (at least one week). Essiccation depends considerably on the amount of oil applied, the kind of wood and temperature.